

Series UPX-FN, Fine Pitch 16:9

Fine

Fine pitch in 16:9 format at a lower price than Fine Slim. For receptions, showrooms and meeting rooms.

Pixel pitch	Brightness	Cabinet	Cabinet weight
0.94 to 1.88 mm	up to 800 nit	600 × 337.5 × 48 mm	7 kg

Same format as Fine Slim, 600 × 337.5 mm, but 48 mm deep and weighing 7 kg. If the wall stays where it is and there is space behind it, you save here.

Contrast 8000:1 and a refresh rate from 3840 Hz. The picture does not flicker, even on camera footage.

16:9 in the cabinet. TV content fits without borders. Four by four cabinets at P1.25 give Full HD.

Mounting to suit the site. Magnetic mounts or fixed brackets, depending on how the wall is built.

Front maintenance. Modules come out from the front with a suction tool. The screen can sit directly against the wall.

Double safeguards. Redundant power supply and signal routing on request.





	P0.94	P1.25	P1.56	P1.87
Pixel pitch	0.9375 mm	1.25 mm	1.56 mm	1.875 mm
LED type	Mini 4 in 1	SMD1010	SMD1010	SMD1010/SMD1515
Module	150 × 168.75 mm	150 × 337.5 mm	150 × 168.75 mm	150 × 168.75 mm
Module resolution	160 × 180 pixels	120 × 270 pixels	96 × 108 pixels	80 × 90 pixels
Pixel density	1 137 800 pixels/m²	640 000 pixels/m²	409 600 pixels/m²	284 444 pixels/m²
Min. viewing distance	1 m	1.25 m	1.56 m	1.87 m
Brightness	400 to 600 nit	400 to 600 nit	400 to 800 nit	400 to 800 nit
Humidity	10 to 75 %	10 to 75 %	10 to 75 %	10 to 95 %

For all variants

Cabinet	600 × 337.5 × 48 mm
Cabinet weight	7 kg
Viewing angle	160° horizontal, 160° vertical
Refresh rate	from 3840 Hz
Max. power	up to 800 W/m²
Avg. power	100–200 W/m²
Operating temperature	–20 to +50 °C
Lifetime	100 000 hours
Maintenance	from the front

Ultimapix
Scherrer Medien GmbH
Neuwiesstrasse 24
CH-8572 Berg TG

+41 71 511 09 90
info@ultimapix.com
ultimapix.com/en/products/fine/

Values as specified by the manufacturer, subject to change. Images may differ from the product, image content is an example.