

Series UPX-TL, Outdoor LED totem P2.9

Totem LED

Freestanding LED totem for squares, stations and shopping streets. It opens at the side, so it is quick to maintain.

Pixel pitch	Brightness	Display area	Protection rating
2.98 mm	up to 6500 nit	1000 × 1750 mm	IP65

The display area measures 1000 × 1750 mm, easy to read at eye level. With 5000 or 6500 nit, the picture stays clear even in direct sunlight.

The front swings open sideways like a door. The technician can reach everything without dismantling the totem.

Opens at the side. Power supplies, control system and modules are accessible behind the front.

Cooled. Air duct at the front, air intake at the bottom, exhaust at the top, with temperature control and dust filter. Heating optional.

Secure. Toughened glass 6 mm or laminated glass 8 mm, IK10. Aluminium housing, corrosion-resistant.

Remote management. Content via LAN or Wi-Fi.





Specifications

Pixel pitch	2.976 mm
Display area	1000 × 1750 mm
Module	250 × 250 mm
Pixel density	112 896 pixels/m²
LED type	SMD1415
Brightness	5000 or 6500 nit
Refresh rate	1920 or 3840 Hz
Viewing angle	170° horizontal and vertical
Glass	6 mm toughened or 8 mm laminated glass, IK10
Protection rating	IP65
Max. power	800 W/m²
Operating temperature	−20 to +50 °C
Cooling	Fans, heating optional
Maintenance	from the front or rear
Housing	Aluminium profile, colour of your choice

Ultimapix
Scherrer Medien GmbH
Neuwiesstrasse 24
CH-8572 Berg TG

+41 71 511 09 90
info@ultimapix.com
ultimapix.com/en/products/totem-led/

Values as specified by the manufacturer, subject to change. Images may differ from the product, image content is an example.